

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Model : TBP60-54FN-W(B)

Bakery Display Cases

Refrigerated Bakery Cases

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



TBP60-54FN-W



TBP60-54FN-B

___ FEATURES & BENEFITS =__

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Attractive, elegant, glass sided Euro design Straight, tempered front & side glass with minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design

visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

■ High-density polyurethane insulation

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

■ Sliding rear doors and front glass opening

Sliding rear doors make it easily accessible and convenient to arrange products. These doors are built to withstand constant sliding open and close. The front glass opens just enough to clean the interior effortlessly.

- Digital temperature controller
- Double pane glass is tempered for safety (Front heated glass)
- Adjustable, tempered glass shelves with AL front and back edges
- Stainless steel airflow grille
- Exterior and bottom glass shelf is white (black) with a mirror finish
- Rear access to compressor compartment for quick and easy service









		# of			Watt	Crated	L x D x H*
Model	CU./FT.	Shelves	HP	AMPS	(W)	Weight (lbs.)	(inches)
TBP60-54FN-W(B)	21.8	2	3/4	8.7	1000.5	741	59 x 271/2 x 517/8

(unit: inch)

Bakery Display Cases

Model: TBP60-54FN-W(B)

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	8.7				
Watt (W)	1000.5				
Compressor HP	3/4				
Cord Length (ft.)	81/4				
Refrigerant	R-290				
DIMENSIONAL DATA	DIMENSIONAL DATA				
Net Capacity (cu. ft.)	21.8				
Ext. Length Overall (in.)	59 (1500mm)				
Ext. Depth Overall (in.)	27 _{1/2} (700mm)				
Ext. Height Overall (in.)*	517/8 (1318mm)				
Shelf Size (L x D) (in.)	56 x 13				
	56 x 15				
# of Shelves	2				
Net Weight (lbs.)	505 741				
Gross Weight (lbs.)					

Design and specifications subject to change without notice.

■ WARRANTY: 2 Year Parts and Labor Warranty **Additional 3 Year Warranty on Compressor**


STANDARD FEATURES

- · Front glass door lock standard
- · Self-contained system, no plumbing required
- · Safety shielded LED interior lighting
- · White and black color come standard
- 3" dia. swivel casters with locks on the rear set
- ** Lead time applies. Please contact your sales representative for more details to order.


■ Recommended operating conditions

TBP models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

PLAN VIEW



FRONT VIEW




Ver.20200807











■ Warranty: 800-381-7770 ■ AC: 888-900-1002











Actual shipping weight may differ due to extra packing materials for product protection.

^{*} Height does not include 2-1/4" for caster height.