

REFRIGERATOR MANUFACTURER
Turbo air
 more durable, efficient, beautiful


4184 E. Conant St.
 Long Beach, CA 90808
 Tel. 310-900-1000
 Fax. 310-900-1077
www.turboairinc.com

| | |
|-----------------|-------|
| Project : | |
| Model # : | |
| Item # : | Qty : |
| Available W/H : | |
| Approval : | |

Vertical Open Display Cases

Extra Deep
 Solid Side Panel

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.

Model : TOM-48DXB-SP(-A)-N



W/ Security cover (optional)



≡ FEATURES & BENEFITS ≡

▪ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

▪ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

▪ Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield optimizes the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application. Ideal for eye-catching displays and convenient access with fast service in high traffic areas.

▪ Interior materials available in two standards

Stainless steel interior for sanitary purposes or black coated interior with mirrored sides for maximized display effects.

▪ Solid side panels used to ensure durability

▪ Standard back-guard improves airflow

▪ Energy saving night curtain standard

▪ Optional security cover available

▪ Foamed with polyurethane, high-density cell insulation (CFC free)

▪ Front air intake and rear air discharge

▪ Perforated interior back wall and top for improved airflow



| Model | CU./FT. | # of Shelves | HP | AMPS | Crated Weight (lbs.) | L x D' x H (inches) |
|---------------------------|-------------|--------------|----------------|-------------|----------------------|-----------------------------|
| TOM-48DXB-SP(-A)-N | 14.9 | 4 | 3/4 x 2 | 15.5 | 727 | 48 x 34 1/4 x 78 7/8 |

Vertical Open Display Cases

Extra Deep
Solid Side Panel

Model : TOM-48DXB-SP(-A)-N

| ELECTRICAL DATA | |
|----------------------------------|--------------------------|
| Voltage | 115/60/1 |
| Plug Type | Ⓢ NEMA 5-20P |
| Full Load Amperes | 15.5 |
| Compressor HP | 3/4 x 2 |
| Refrigerant | R-290 |
| DIMENSIONAL DATA | |
| Net Capacity (cu. ft.) | 14.9 |
| Ext. Dimension (L x D x H) (in.) | 48 x 34 1/4 x 78 7/8 |
| Int. Dimension (L x D x H) (in.) | 45 1/4 x 21 1/4 x 48 3/4 |
| Net Weight (lbs.) | 562 |
| Gross Weight (lbs.) | 727 |
| # of Shelves | 4 |
| Shelf Size (in.) | 45 1/4 x 16 |
| Power Cord Length (in.) | 118 1/8 |

Design and specifications subject to change without notice.
Actual shipping weight may differ due to extra packing materials for product protection.
* Depth does not include 1-5/8" for safety bar and 1-1/8" for rear bumper.

WARRANTY : 2 Year Parts and Labor Warranty
Additional 3 Year Warranty on Compressor

STANDARD FEATURES :

- Simple plug-in installation
- Patented self-contained system, no plumbing required
- Standard color comes in black only
- LED interior lighting
- Recommended operating conditions:


TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

OPTIONAL ACCESSORIES :


- Security cover: SC-48-DXB
- Price tag channel: P48DX000ZK (45"L)

PLAN VIEW

(unit : inch)




PLAN VIEW



FRONT VIEW

Controller & Power Lamp switch

SIDE VIEW



SIDE VIEW - INSIDE

Ver.20181210



- Turbo Air : 800-627-0032
- GK : 800-500-3519
- Warranty : 800-381-7770
- AC : 888-900-1002

REFRIGERATOR MANUFACTURER
Turbo air

GERMAN KNIFE

RADIANCE

REFRIGERATION SYSTEM
Turbo air

TEXAKING