

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Model # : Item # :

Qty :

Available W/H :

Approval :

Sandwich / Salad Unit

Food Prep Tables E-line





____ FEATURES & BENEFITS =___

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Cold air compartment

Our innovative "Cold Air Compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

Cabinet construction

E-line model boasts an AL exterior (galvanized steel back and bottom). Interior is stainless steel floor and back with AL sides. It guarantees the utmost in cleanliness and long product life.

Convenient cutting board side rail

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included
- 9-1/2" deep, ½" thick cutting board included
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 39°F for the best in food preservation

							ATURAL Refrigerant		tertek
Model	Swing Door	CU./FT.	#of Shelves	#of Pans	#of Hood	HP	AMPS	Crated Weight (lbs.)	$L \ge D^* \ge H^{\dagger}$
EST-48-N	2	12	2	12	1	1/4	4.4	242	481/4 x 30 x 37

Ver.20190412

* Depth does not include 1" for rear spacers. † Height does not include 5-1/2" for caster height.

Sandwich / Salad Unit

(unit : inch)

Model : EST-48-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	(i) NEMA 5-15P				
Full Load Amperes	4.4				
Compressor HP	1/4				
Cord Length (ft.)	9				
Refrigerant	R-290				
DIMENSIONAL DATA					
Ext. Length Overall (in.)	481/4 (1225mm)				
Ext. Depth Overall (in.) *	30 (762mm)				
Ext. Height Overall (in.)†	37 (939mm)				
# of Doors	2				
# of Shelves	2				
# of Pans	12				
Net Capacity (cu. ft.)	12				
Shelf Size (in.)	211/2 x 167/8				
Net Weight (lbs.)	225				
Gross Weight (lbs.)	242				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1" for rear spacers.

† Height does not include 5-1/2" for caster height.


WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

STANDARD FEATURES

- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Standard 1/6 size, 4" deep condiment pans included


OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, 1/2" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Removable food cover: RCT-48
- Stainless steel double overshelf: TSOS-4R



PLAN VIEW

TOP VIEW



SIDE VIEW

Ver.20190412



(GERMAN)

KNIFE

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002

Turbo air Texaking

