

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | |
|-----------------|------|
| Model #: | |
| Item #: | Qty: |
| Available W/H : | |
| Approval : | |

Undercounter Freezer

<u>Undercounters</u> M3 Series

Model: MUF-28-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



___ FEATURES & BENEFITS =__

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

- Digital temperature control & monitor system
 - Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.
- Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides and back. It guarantees the utmost in cleanliness and long product life. The M3 model adds a touch of style to the most refined setting.

Adjustable, heavy duty, PE (polyethylene) coated wire shelves

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

Magnetic door gaskets

Magnetic door gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

- Field reversible hinge
- LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

■ Freezer holds -10°F ~ 0°F for the best in frozen food preservation













| Model | Swing Door | CU./FT. | #of Shelves | НР | AMPS | Crated Weight (lbs.) | L x D [*] x H [†] (inches) |
|----------|---------------|---------|----------------|-----|------|-------------------------|--|
| MUF-28-N | 1 | 6.97 | 1 | 1/3 | 2.4 | 163 | 271/2 x 30 x 305/8 |

(unit: inch)

Undercounter Freezer

Model: MUF-28-N

| ELECTRICAL DATA | | | | | |
|----------------------------|------------------------|--|--|--|--|
| Voltage | 115/60/1 | | | | |
| Plug Type | ① NEMA 5-15P | | | | |
| Full Load Amperes | 2.4 | | | | |
| Compressor HP | 1/3 | | | | |
| Cord Length (ft.) | 9 | | | | |
| Refrigerant | R-290 | | | | |
| DIMENSIONAL DATA | IMENSIONAL DATA | | | | |
| Net Capacity (cu. ft.) | 6.97 | | | | |
| Ext. Length Overall (in.) | 271/2 (699mm) | | | | |
| Ext. Depth Overall (in.)* | 30 (762mm) | | | | |
| Ext. Height Overall (in.)† | 305/8 (777mm) | | | | |
| # of Doors | 1 | | | | |
| # of Shelves | 1 | | | | |
| Net Weight (lbs.) | 146 | | | | |
| Gross Weight (lbs.) | 163 | | | | |
| Shelf Size (in.) | 22 _{1/2} x 17 | | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- Standard 4" dia. swivel casters with locks on the front set

■ OPTIONAL ACCESSORIES:

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional PE coated wire shelf: WM27800100
- ☐ Back splash guard: TU-28B
- □ Door lock: extra lead time will apply, please call factory for more details to order

PLAN VIEW





SIDE VIEW

Ver.20190403


























^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5" for caster height.