

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

Undercounter Refrigerator - Drawers

Undercounters Super Deluxe Series

Model: TUR-60SD-D4-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



= FEATURES & BENEFITS =

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system Keep food products safe by maintaining constant temperatures.

Keep food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Stainless steel cabinet construction

The Turbo Air Super Deluxe model boasts a stainless steel interior and exterior (galvanized steel back & bottom). It guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ Magnetic door gaskets

Magnetic door gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.

 Refrigerator holds 33°F ~ 38°F for the best in food preservation













Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
TUR-60SD-D4-N	ı	16	ı	1/5	2.4	301	601/4 x 30 x 305/8

Model: TUR-60SD-D4-N

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type					
Full Load Amperes	2.4				
Compressor HP	1/5				
Cord Length (ft.)	9				
Refrigerant	R-290				
DIMENSIONAL DATA					
Net Capacity (cu. ft.)	16				
Ext. Length Overall (in.)	60 _{1/4} (1530mm)				
Ext. Depth Overall (in.)*	30 (762mm)				
Ext. Height Overall (in.)†	305/8 (777mm)				
# of Doors	-				
# of Shelves	-				
Net Weight (lbs.)	263				
Gross Weight (lbs.)	301				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

3 Year Parts and Labor Warranty **Additional 2 Year Warranty on Compressor**


STANDARD FEATURES

- · Anti-corrosion coated evaporator
- · Self-contained system
- · Standard 4" dia. swivel casters with locks on the front set


■ OPTIONAL ACCESSORIES:

- ☐ 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" ABS plastic leg: 30221M0200
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Back splash guard: TU-60B
- ☐ Stainless steel double overshelf: TSOS-5R

PLAN VIEW (unit: inch)



PLAN VIEW



SIDE VIEW

Ver.20181212





lurbo air















^{*} Depth does not include 1" for rear spacers.

[†] Height does not include 5" for caster height.