



Project _____
AIA # _____ SIS # _____
Item # _____ Quantity _____ C.S.I. Section 114000

RMC SERIES

MILK COOLER

16 CRATE CAPACITY MODELS



Model Shown - RMC49D4



Models listed to the applicable UL, CSA and NSF standards by an approved NRTL. Consult the factory or unit data plate for additional information.

STANDARD PRODUCT FEATURES

- Energy Efficient Refrigeration System, Using R290 Refrigerant
- Thermostatic Expansion Valve Metering Device
- Stainless Steel Exterior & Interior
- Electronic Control
- Top Mounted Removable Refrigeration System
- Forced Air Refrigeration System
- Accommodates (16) 13" x 13" Crate(s) or (8) 13" x 19" Crate(s)
- Single or Double Sided
- Low Access Point
- Sliding Lift Up & Down Door(s)
- Reinforced Cabinet Exterior Bottom
- Heavy Duty Dunnage Racks Protect Cabinet & Promote Airflow
- Durable Caster Rail System for Flexible Positioning
- Lockable Insulated Doors
- Metal Door Handles
- Magnetic Snap-In EZ-Clean Door Gasket(s)
- Floor Drain with Plug
- 6' Cord & Plug Attached
- Set of Six (6) 4" Factory Mounted Adjustable Casters

AVAILABLE CONFIGURATIONS

Single Access Models

RMC58S4 16 Crate 58" Length, 4" Casters

Double Access Models

RMC58D4 16 Crate 58" Length, 4" Casters

ACCESSORIES & OPTIONS (*field installed)

- Set of (6) 6" Adjustable Casters, field installed
- MCACC-BUMPER, Bumper Corner Guard Kit (4), field installed
- RMCACC-SYS34, Milk Cooler Refrigeration System Replacement (Compatible only with models using R290 Refrigerant)


Approved by _____ Date _____ Approved by _____ Date _____

MODELS


Single Access Model: RMC58S4

Double Access Model: RMC58D4

Single Access Models (58" models have 6 casters)



Double Access Models (58" models have 6 casters)





RMC SERIES

MILK COOLER

16 CRATE CAPACITY MODELS

MODELS

Single Access Models: RMC58S4
Double Access Models: RMC58D4

EQUIPMENT SPECIFICATIONS

| MODELS | RMC58 |
|---------------------------------------------------------------|--------------------|
| DIMENSIONAL DATA | |
| Net Crate Capacity 13 x 13 in. ¹ | 16 |
| Net Crate Capacity 13 x 19 in. ¹ | 10 |
| Length (L)-Overall in. | 58 (147.3 cm) |
| Depth-Single Cabinet Only in. | 32 1/8 (81.6 cm) |
| Depth-Double Cabinet Only in. | 34 1/4 (87 cm) |
| Height-Overall on 4" Casters | 46 (116.8 cm) |
| Net Weight uncrated lbs. (kg) | 568 (258) |
| ELECTRICAL DATA (NEMA 5-15P attached) | |
| Voltage | 115/60/1 |
| Single & Dual Access Full Load Amperes kWk/Day ² | 3.2 2.36 kWk/Day |
| Single Access Cabinet Volume | 21.18 |
| Double Access Cabinet Volume | 22.53 |
| REFRIGERATION DATA | |
| Refrigerant | R-290 |
| Refrigerant Amount oz. | 2.5 (70.9 g) |
| BTU/HR ³ H.P. | 2100 1/4 H.P. |

NOTE:

- * Figures in parentheses reflect metric equivalents.
- 1. Net Capacity cu. ft.
- 2. kWk/Day = Kilowatt usage per 24 hours.
- 3. Based on a 90°F ambient and 20°F evaporator.

When ordering please specify: Voltage, Hinging, and Options.

Equipped with one NEMA 5-15P Plug



CONSTRUCTION, HARDWARE, INSULATION

Cabinet exterior and interior is constructed of stainless steel. Interior sides, back and front are also stainless steel. The exterior cabinet bottom is constructed of stainless steel.

Gasket profile and material simplify cleaning and increase overall gasket life.

Both the cabinet and doors are insulated with non-CFC, foamed in place polyurethane.

DOOR/ACCESS

Front sliding protects gasket(s). Lockable lift up top access door.

REFRIGERATION SYSTEM

A balanced, top mounted side and front and rear breathing, refrigeration system using environmentally friendly, low GWP R-290 refrigerant is provided. It features an air-cooled hermetic compressor, thermostatic expansion valve metering device, and a forced air evaporator coil. An 6' cord and plug is provided. Standard operating temperature is 34° to 38°F (1.1° to 3.3°C).

CONTROLLER

An electronic digital control is supplied standard. It includes a 3-Digit LED display, and a Fahrenheit or Celsius temperature scale display capability.

INTERIOR/DUNNAGE RACKS

Heavy duty removable dunnage racks protect cabinet and promote airflow.

WARRANTIES

Both a six year parts and labor warranty and seven year compressor parts warranty.

CONTINUED PRODUCT DEVELOPMENT MAY NECESSITATE SPECIFICATION CHANGES WITHOUT NOTICE.