

# TRUE MANUFACTURING CO., INC. RETAIL DIVISION

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com

Project Nan	AIA #	
Location: _		
Item #:	Qty:	SIS #
Model #:		

Model:

CVM-13-HC~EGC01

**Contemporary Visual Merchandiser:** 

Swing Door Refrigerator with Hydrocarbon Refrigerant~Edge Glass Curved Version 01



## **FEATURES**

With its curved edge design and increased beverage storage, the series redefines merchandising

The curved-edged door design has a built-in handle for opening the door from the top or side.

Illuminated handle position indicator.

Uses environmental friendly R290 Hydrocarbon refrigerant.

Energy efficient, factory balanced, refrigeration system holds 33°F to 38°F (.5°C to 3.3°C).


Self-Cleaning RCU Technology eliminates the need for cleaning of condenser coil, reduces energy consumption and helps maintain the coldest temperature and freshest product.

### ROUGH-IN DATA

 $Specifications \ subject \ to \ change \ without \ notice.$  Chart dimensions rounded up to the nearest \%" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)						NEMA	Cord Length (total ft.)	Crated Weight (lbs.)
Model	Doors	Shelves	W	D†	Н	HP	Voltage	Amps		(	(kg)
CVM-13-HC~EGC01	1	5	24%	22%	63¾	1/5	115/60/1	2.5	5-15P	10	235
			630	581	1617	N/A		N/A		3.05	106

† Depth does not include 1" (26 mm) for rear bumper.



Model:

CVM-13-HC~EGC01

## **Contemporary Visual Merchandiser:**

Swing Door Refrigerator with Hydrocarbon Refrigerant~Edge Glass Curved Version 01



## STANDARD FEATURES DESIGN

 True's Contemporary Series is built with durability, stability, and style in mind. Through the series' curved edge design it redefines merchandising with its inspired product displays and increased beverage storage.

#### **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- NSF/ANSI Standard 7 compliant for the storage and/or display of packaged or bottled product.

#### **CABINET CONSTRUCTION**

- Exterior non-peel or chip black powder coated cold rolled steel; durable and permanent.
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.

- Door sign decal. Variety of decal options available.
- Interior attractive, black aluminum interior liner with stainless steel floor.
- Insulation entire cabinet structure is foamedin-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Frame rail fitted with leg levelers.
- 2" integrated rollers standard.

#### DOOR

- "Low-E", double pane thermal insulated glass door assembly with mitered plastic channel frame. The latest in energy efficient technology.
- The door features an integrated LED handle indicator for a sleek, modern appearance.
- Self closing door. Positive seal, torsion type closure system.
- Magnetic door gasket of one piece construction, removable without tools for ease of cleaning.
- Edge door will not change when an alternative interior or exterior finish is ordered.

#### SHFIVING

 Five (5) adjustable, heavy duty PVC coated wire shelves 20%"L x 17½"D (524 mm x 445 mm). Four (4) chrome plated shelf clips included per shelf.  Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on ½" (13mm) increments.

#### LIGHTING

• LED interior lighting, safety shielded.

#### **ELECTRICAL**

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet.
 Cord and plug set included.




#### **OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply.

- ☐ White exterior.
- ☐ Stainless steel interior and exterior.
- ☐ White aluminium interior liner with white shelving.
- □ 2 ½" (64 mm) diameter castors.
- ☐ Red wine thermostat.
- ☐ White wine thermostat.
- ☐ Chocolate thermostat.
- ☐ Additional shelves.
- ☐ TrueFlex gravity feed organizers.
- ☐ True Flex-Pac kit.
- ☐ Pricing strips.

### PLAN VIEW



METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

KCL	Model	Elevation	Right	Plan	3D	Back
	CVM-13-HC~EGC01					