



Refrigeration Equipment Manufacturer

Undercounter Refrigerator

U2CRR-16S

Description: Two solid door deep undercounter refrigerator, 16 cu. ft

Features & Benefits

Stainless steel interior and exterior for greater durability, construction and appearance.

Self-contained **side-mounted** refrigeration system for larger storage capacity and high humidity coated **fin coil** evaporator.

"Auto-D" automatic electric defrost on refrigerator prevents evaporator from freezing.

- Holds 25° F to 42° F for refrigerator

Exterior computerized thermometer and temperature control with LED display. **Temperature setting is easy, fast and accurate.**

2.5" thick, foamed-in-place polyurethane high density insulation.

Four adjustable epoxy-coated steel wire shelves. 5" casters standard. **Easy mobility and installation.**

16 gauge, 300 series stainless steel top.

Heavy-duty overall construction for high-volume, constant duty operation.

Adjustable tension spring loaded doors.

Electric condensate evaporator - **no floor drain required!**

Dimensions	W	D	H
Exterior (inches)	61.5	29.5	29.8
(height with casters)			34.8
Pallet size (inches)	67.8	31.5	4.5

General Information	Cubic Feet Shelves	
Refrigerator	16	4
Shelf size:	22" x 24"	
Exterior:	Stainless	
Interior:	Stainless	
Unit Weight (lbs.)	275	
Gross weight (lbs.)	320	
Cord length (inches)	79	
Nema:	5-20p	

Compressor Information	# compressors	Refrigerant Capacity
Refrigerant R134A	1	High/Medium Temp
Use	H.P	.
Refrigerator	1/5	

Volts	115
Amps	4.59 (run) 6.89 (start)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

TOP VIEW

