Models:
☐ U60-10RR

☐ U60-10RS

☐ U60-10SS

U Series 60" Gas Restaurant Range

☐ U60-8G12RR

☐ U60-8G12RS

☐ U60-8G12SS

Item:
Quantity:
Project:
Approval:
Date:

☐ U60-G60RR

☐ U60-G60RS

☐ U60-G60SS

	1	
	S	ta La
		La
		St
		St
		St
		ak
		12
		tr
		6"
The state of the state of		La G
		G
	St	an
		Ca

Model U60-10RR

NOTE: Ranges supplied with casters must be installed with an approved restraining device.

Standard Features:

• Large 27" (686mm) work top surface

U60-4G36RR

U60-4G36RS

☐ U60-4G36SS

- Stainless steel front and sides
- Stainless steel 5" (127mm) plate rail
- Stainless steel backguard, w/removable stainless steel shelf
- 12" (305mm) section stamped drip trays w/ dimpled bottom
- 6" (152mm) adj. stainless steel legs
- Large easy-to-use control knobs
- Gas regulator

☐ U60-6G24RR

☐ U60-6G24RS

☐ U60-6G24SS

Standard on Applicable Models:

- Cabinet base in lieu of oven
- Ergonomic split cast iron top ring grates
- Powerful 32,000 Btuh/ 9.37 kW 2 piece cast iron geometric open top burner
- 5/8" (15mm) thick steel griddle plate w/manual hi/lo valve control, 23" (584mm) working depth surface, Standard on right, optional on leftt
- 4-1/4" (108mm) wide grease trough
- 18,000 Btuh/5.27 kW cast iron "H" style griddle burner per 12"(305mm) width of griddle
- 38,000 Btuh/ 11.13 kW cast iron "H" style oven burner
- Snap action modulating oven thermostat low to 500° F
- Large oven w/porcelain ribbed bottom & door, aluminized steel top, sides and back; oven fits standard sheet pans in both directions for standard ovens
- Nickel plated oven rack and 3-position removable oven rack guide

Strong, keep-cool oven door handle

Series 60" Gas Restaurant Ranc

 Convection oven w/3 nickel plated oven racks and removable rack guides in lieu of standard oven w/ 1/3HP 120v 60 Hz single phase fan motor; change suffix RS to CS or RR to CR (1) or CC (2) convection ovens, CR or CS ovens standard on right

Optional Features:

☐ U60-2G48RR

☐ U60-2G48RS

☐ U60-2G48SS

- Convection oven motor 240v 50/60HZ single phase
 - Snap action modulating griddle control 175° to 425° F
- Grooved griddle in 1/2 or full plate section widths
- Hot top 12" (305mm) plate in lieu of two open burners, manual valve controlled w/18,000 Btuh/5.27 kW cast iron "H" burner standard on left side
- □ Low profile 9-3/8" (238mm) backguard stainless steel front and sides
 □ Stainless steel back for high shelf,
- low profile backguard or range

 Additional oven racks
- 6" (152mm) levelling swivel casters (4), w/front locking
- Flanged deck mount legsTwo stainless steel doors for storage
- base models

 Intermediate stainless steel shelf for
- Intermediate stainless steel shelf for storage base models

Specifications:

Gas restaurant series range with deep capacity oven. 59-1/16" (1500mm) wide with 27" (686mm) deep work top surfaces. Stainless steel front, sides and 5" wide front rail. 6" (152mm) legs with adjustable feet. Ten powerful 2 piece 32,000 Btuh/9.37 kW (Natural Gas), cast open burners set in split cast iron ergonomic grates. Griddle or optional hot-top with cast iron "H" style burners, 18,000 Btuh/5.27 kW (natural gas), in lieu of open burners. Porcelain oven bottom and door

liner. Durable heavy duty oven door w/ "keep cool" handle. Heavy cast iron "H" oven burner rated 38,000 Btuh/11.13 kW (natural gas) Oven controlled by even bake, fast recovery snap action modulating oven thermostat. Available with convection oven or storage base in lieu of standard oven(s).









Garland 1333 East 179th Street Cleveland, Ohio 44110 Phone: 800-424-2411 Fax: 800-624-0218 Garland Commercial Ranges Ltd 1177 Kamato Road, Mississauga, Ontario L4W 1X4 CANADA Phone: 905-624-0260 Fax: 905-624-5669



327

OB=Open Burn		G=Grid	O=Oven(s)			
Model				Total	Ship Wt.	
Number	ОВ	G	0	BTU/Hr Natural	Lbs.	Kg
U60-10RR ¹	10	_	(2) 26"	396,000	726	329
U60-10RS ¹	10	_	(1) 26"	358,000	690	312
U60-10SS	10	_	_	320,000	581	264
U60-8G12RR ¹	8	12"	(2) 26"	350,000	756	343
U60-8G12RS ¹	8	12"	(1) 26"	312,000	720	327
U60-8G12SS	8	12"	_	274,000	611	277
U60-6G24RR ¹	6	24"	(2) 26"	304,000	791	359
U60-6G24RS ¹	6	24"	(1) 26"	266,000	755	342
U60-6G24SS	6	24"		228,000	646	293

Shipping volume, all models=79 Cu Ft							
Model				Total	Ship Wt.		
Number	ОВ	G	0	BTU/Hr Natural	Lbs.	Kg	
U60-4G36RR ¹	4	36"	(2) 26"	258,000	826	375	
U60-4G36RS ¹	4	36"	(1) 26"	220,000	790	358	
U60-4G36SS	4	36"	_	182,000	681	309	
U60-2G48RR ¹	2	48"	(2) 26"	212,000	851	386	
U60-2G48RS ¹	2	48"	(1) 26"	174,000	815	370	
U60-2G48SS	2	48"	_	136,000	706	320	
U60-G60RR ¹	_	60"	(2) 26"	166,000	866	393	
U60-G60RS ¹		60"	(1) 26"	128,000	830	376	

60"


90,000


or one convection oven or CC for two convection ovens

Width In (mm)	Width Depth ² w		ight Oven Interior-in (mm)		Combustible Wall Clearance-In (mm)		Entry Clearances In (mm)		Manifold Operating Pressure		
in (mm)	in (mm)	In (mm)	Height	Depth ³	Width	Sides	Rear	Crated	Uncrated	Natural	Propane
59-1/16	34-1/2	57	13	26	26-1/4	14	6	37	36-1/2	4.5" WC	10" WC
(1500)	(876)	(1448)	(330)	(660)	(667)	(356)	(152)	(940)	(927)	11 mbar	25 mbar

U60-G60SS

Gas input ratings shown for installations up to 2000 ft.,(610m) above sea level. Please specify altitudes over 2000 ft.






Burner Ratings (BTU/Hr/kW)								
Gas Type	Gas Type Open Top		Standard Oven or Convection					
Natural	32,000/9.37	18,000/5.27	38,000/11.13					
Propane	26,000/7.61	18,000/5.27	32,000/9.38					

Note: Installation clearance reductions are applicable only where local codes permit.

This product is not approved for residential use.

Convection ovens with 120V, 60 Hz, 1 phase, 3.4 amps motors are supplied with 6'/1829mm cord and plug (NEMA 5-15P); 240V ,50/60 Hz, 1 phase motors are not supplied with cord and plug and must have direct connect.



Form# U60 Series (01/04/11)

Garland 1333 East 179th Street Cleveland, Ohio 44110 Phone: 800-424-2411 Fax: 800-624-0218

Garland Commercial Ranges Ltd 1177 Kamato Road, Mississauga, Ontario L4W 1X4 CANADA Phone: 905-624-0260 Fax: 905-624-5669



² Convection oven base models add 3 7/8" (98mm) to the depth of the unit. ³ Convection oven depth 22" (559mm)