## HOLDING & TRANSPORT

# **VULCAN**



UL listed. UL listed to Canadian safety standards. Classified by UL to NSF Std. #4.

#### **SPECIFICATIONS**

Vulcan Hart Model No. VBP heated holding and transport cabinets. Blower motor for gentle and even temperature distribution. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid) (VBP5I has 3" casters). Recessed control panel containing heating indicator light, analog thermometer, and full range thermostat for temperatures up to 190°F (88°C). Cabinet will hold 18" x 26" sheet pans, 12" x 20" steam table pans, or a combination of both on 11/2" centers. Complete with universal tray slides adjustable on 11/2" centers. Cabinet interior and exterior are both constructed out of 20 gauge stainless steel. Recessed sidemounted handles, magnetic action door latch, and full insulation; 11/2" in side walls and 2" in top. Integrated steel frame for maximum strength. Field reversible doors. Complete with top mounted cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts. Lifetime warranty on heating elements.

# **VBP SERIES**

Item #

# **HOLDING & TRANSPORT CABINETS**

- U VBP5I Holding & Transport Cabinet
- U VBP7I Holding & Transport Cabinet
- U VBP13I Holding & Transport Cabinet
- U VBP15I Holding & Transport Cabinet
- U VBP77I Holding & Transport Cabinet

#### STANDARD FEATURES

- Holding Capacity:
  - 18" x 26" sheet pans
  - 12" x 20" pans, or a combination of both on 11/2" centers
- Blower motor for gentle and even temperature distribution
- Dutch doors (VBP15I only)
- 5" heavy duty casters (2 swivel with brakes and 2 rigid) (3" on VBP5I)
- Recessed side mounted handles
- Recessed control panel
- Heating indicator light
- Analog thermometer
- Full range thermostat for temperatures up to 190°F (88°C)
- Universal tray slides adjustable on 1<sup>1</sup>/2" centers.
  VBP15I, VBP13I & VBP77I ship with 10 pairs of tray slides.
  VBP7I & VBP5I ship with 5 pairs.
- Interior and the exterior are both constructed out of 20 gauge stainless steel
- Fully insulated with 1<sup>1</sup>/<sub>2</sub>" in side walls and 2" in top
- Integrated steel frame for maximum strength
- Magnetic action door latch
- Field reversible doors
- Top mounted cord
- Complete with cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts
- Lifetime warranty on the heating elements

#### **OPTIONS**

- □ 208/240 volt
- Humidity pan
- Full perimeter bumper
- Glass Dutch doors
- □ VRH oven racking available for VBP7I, VBP77I, and VBP15I
- Wire shelves to sit on tray slides
- □ Electronic control with digital display (120V only)
- Transport latch
- Additional tray slides

# **VULCAN**

a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

#### A City Discount

# HOLDING & TRANSPORT

### **VULCA**N **VBP SERIES HOLDING & TRANSPORT CABINETS** DOOR SWING 52.75" (1340 mm) Drawings shown with optional bumper All Models Top View w 0=0 T 0=0 ম্য ম Π ম Π Z **VBP5I Front & Side Views VBP7I Front & Side Views** D w w D 0-0 w D 0=0 . 0=0 স S S ম N ম্য **VBP13I Front & Side Views VBP15I Front & Side Views VBP77 Front & Side Views**

MODEL	DIMENSIONS	CAPACITY		ELECTRICAL			SHIPPING WEIGHTS	
	EXTERIOR	12" x 20" x 2½" PANS	18" x 26" SHEET PANS	VOLTS	WATTS	AMPS	LBS	KG
VBP5I	25" W x 33" D x 301/2" H	10	5	120	1,000	8.3	173	79
VBP7I	25" W x 33" D x 39" H	14	7	120	1,000	8.3	198	90
VBP13I	25" W x 33" D x 60" H	26	13	120	1,200	10	270	123
VBP15I	25" W x 33" D x 65¼" H	30	15	120	1,200	10	297	135
VBP77	25" W x 33" D x 72" H	28	14	120	1,000*	8.3*	342	155

\*per compartment

Optional bumper adds  $31\!/\!\!4"$  to the width and  $15\!/\!\!8"$  to the depth.



P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

F45414 (10/12)

NOTE: In line with its policy to continually improve its products, Vulcan reserves the right to change materials and specifications without notice.