

Project:	
Location:	
Item #:	
Quantity:	

## **Big Top Salad/Sandwich Refrigerators**

**Two Section Model with Doors** 

VUR-4-12BT VUR-4-18BT

Doors, tops and interior floor of stainless steel. Aluminum ends and interior.



## **Standard Features:**

- Stainless Steel Doors, Tops and Interior Bottom Construction Provides Durable Lasting Finish
- Durable Aluminum Interior Sides and Rear for Easy Cleaning
- Models are Front-Breathing and Recessible to Enable Zero Clearance Placement or in Limited Access Areas
- Food Pans are Recessed into an Insulated 2" Top which Surrounds Pans with an Insulated Airflow to Maintain Consistent Temperature
- Holds Food Safely and Assures Fresher Food
- Exclusive Design Accepts 4" and 6" Pans which Maximize Airflow and Maintain Temperature
- A Complete Set of 4" Deep Plastic Pans are Included
- Interior Thermometer Consistently Monitors Temperature
- Spacious Design with 8.5" Cutting Board Provides Maximum Work Surface and Condiment Storage Capacity
- Removable Stainless Steel Insulated Telescoping Lid Offers Easy Cleaning
- Self-Closing Door with Replaceable One-Piece Magnetic Gasket Maintains Positive Seal
- Horizontal Recessed Heavy-Duty Handles Provide Quicker, Easier Access to Cabinets
- · Adjustable Shelves Provide Storage Flexibility

- Heavy-Duty, Epoxy Coated Steel Shelves Accept Heavy Loads and Offer Easy Clean-up
- Energy Saving, High Density, Polyurethane Foam Insulation Promotes Cold Retention
- Anti-Corrosion Coated Evaporator Coil Assures Lasting Performance
- Automatic Condensation Evaporation System Eliminates the Need for a Floor Drain
- Balanced Energy Efficient Refrigeration System
- Environmentally Friendly R-134a Refrigerant
- Plugs into Standard 115 V Outlets Cord and Plug Attached for Easy Installation
- 5" Heavy-Duty Swivel Casters with Brakes Provide Mobility
- · Completely Finished and Enclosed Cabinet Back
- Meets Tough NSF Standard 7, 41°F

## **Optional Features and Accessories:**

- 3" Heavy-Duty Swivel Casters with Brakes
- 6" Adjustable Stainless Steel Legs
- · Single and Double Overshelf
- · Stainless Steel Back
- Door Mounted Dial Thermometer
- · Cylinder Locks

Approvals:






Victory Refrigeration specification sheets are available online at www.victory-refrig.com.

CHARACTERISTICS	VUR-4-12BT	VUR-4-18BT	
Width, Overall	48	48	
Depth, Overall	34	34	
Height, Overall	46 46		
Height, Work Area	36	36	
Capacity Net (cubic feet)	12.6	12.6	
No. of Full Doors	2	2	
No. of Shelves	4 4		
No of 1/6 Size Pans	12	18	
Cabinet Voltage	115/60/1	115/60/1	
Condensing Unit Voltage	115/60/1	115/60/1	
Condensing Unit Size (HP)	1/5	1/5	
Total Amperes	4.8	4.8	
NEMA Receptacle Required	5-15R	5-15R	

Crated dim. & wts.	Ht.	Width	Depth	Lbs.
VUR-4-12BT	481/2	531/2	391/2	280
VUR-4-18BT	48 <sup>1</sup> / <sub>2</sub>	531/2	39 <sup>1</sup> / <sub>2</sub>	275

Dimensional tolerance ± 1/4" Metric dimensions (MM)



Continuous product development may necessitate specification changes and design without notice.



Victory participates in the KCL CADalog, the most current source of CAD symbols for foodservice designers worldwide. Symbols include standard equipment in plan, side, front and 3-D views, layered for FEDA/FCSI recommended guidelines.