

Project:

Item Number:

Quantity:

## **HEAVY-DUTY SLICERS**









Heavy-Duty Slicers

# **DESCRIPTION**

Vollrath's five heavy-duty slicers, all with 12" (30.5 cm) blades and a non-stick coating, are designed to meet the challenges of any high-use operation.

## STANDARD FEATURES

- ☐ Exclusive non-stick coating great for cutting cheese
- ☐ Vollrath's rock solid guides will not flex, giving straight slices every time
- ☐ Heavy-weight meat pusher pushes meat into blade more effectively for easier cuts and less user fatigue
- One-piece, hard-coated anodized aluminum body eliminates food traps and provides light weight with high durability
- ☐ Precision spacing cam for more accurate thickness cutting
- ☐ Low-friction carriage system provides outstanding smooth glide motion
- ☐ Sand-molded, anodized base will never tarnish
- Built-in easy to use two stone sharpener makes blade sharpening simple and convenient
- ☐ Thermal overload protection with manual reset automatically shuts off slicer to protect from damage
- ☐ Easy-tilt product feeder mechanism makes it easy to clean safely without the product feeder dropping
- □ 5 ft. (1.5 m) cord with plug

## **MODELS**

40849 SLR7012/N Belt Driven

40797 SLR 7712/N Belt Driven with Safe Blade Removal System

40799 SLR7512/N Gear-Driven

40801 SLM0012/N Belt Driven with Maximum Clearance

Receiving Tray and Safe Blade Removal

40800 SLR7912/N Automatic Slicer with Safe Blade Removal

#### **FEATURES**

#### **Belt Driven**

- ☐ Heavy-duty slice adjustment for precise and consistent slice thickness
- Centered blade and gauge plate ensure stability under the toughest conditions

#### **Gear Driven**

 Direct drive gear transmission provides the power and robustness for high-volume slicing of cheese and meat

#### **Maximum Clearance Receiving Tray**

- ☐ Special clear slice exit design provides unobstructed receiving tray area for easier slicing and cleaning
- ☐ Extended 1¼" (3.175 cm) maximum slice thickness for greater versatility

### **Automatic Carriage**

- Automatic carriage slices approximately 40 slices per minute for maximum operational efficiency
- ☐ Intuitive setup includes simple main switch and variable speed control
- ☐ Can also be used manually

#### **MODEL COMPARISON**

Feature	40849	40797	40799	40801	40800
Non-Stick Coating	Х	Х	Х	Х	Х
Accommodates Vegetable Chute	Х	Х	Х	Х	Х
Automates Frozen Food Blade	Х	Х	Х	Х	Х
Safe Blade Removal System		Х		Х	Х
Gear Drive			Х		
Belt Drive	Х	Х		Х	Х
Kickstand					Х
Max Clearance Receiving Tray				Х	
Automatic Cartridge					Х

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to the Vollrath Equipment and Smallwares Catalog.

Approvals	Date		

# **Agency Listings**





Due to continued product improvement, please consult www.vollrathco.com for current product specifications.



Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462

# **HEAVY-DUTY SLICERS**

40849 SLR7012/N Belt Driven

SLR 7712/N Belt Driven with Safe Blade Removal System 40797


40799 SLR7512/N Gear-Driven 40801 SLM0012/N Belt Driven with Maximum Clearance Receiving Tray and Safe Blade Removal


40800 SLR7912/N Automatic Slicer with Safe Blade Removal


## **DIMENSIONS**


Dimensions shown in inches (cm).

#### 40849 / 40797










Front View


Side View

Front View

Side View


#### 40801






40800

40799





Front View

Side View

# **SPECIFICATIONS**

		Slicing Capacity					
Item	Drive	Processed Meats	Cheese	HP	Voltage	Amps	Plug
40849	Belt	3 hr/day	1 hr /day or less	1/2	110	2.5	5-15P
40797	Belt	3 hr/day	1 hr /day or less	1/2	110	2.5	5-15P
40799	Gear	Continuous	Continuous	1/2	110	2.5	5-15P
40801	Belt	Continuous	3 hr/day	2/3	110	2.5	5-15P
40800	Belt	Continuous	Continuous	3/4	110	4.7	5-15P

#### Receptacle





The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A. Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560 Main Fax: 800.752.5620 or 920.459.6573

Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462