



Project:

Item Number:

Quantity:

CM-24 Twin Well 4-Qt. Rethermalizer and SS-4 Warmer

The Vollrath Company, L.L.C.

**CM-24 TWIN WELL 4-QT. RETHERMALIZER AND SS-4 WARMER**



<b>MODELS:</b> 72045	120V AC, 1100W
72040	120V AC, 1100W
72425	120V AC, 350W
72430	120V AC, 350W

**CM-24 TWIN-WELL RETHERMALIZER FEATURES**

- Individual controls for merchandising soups with different temperature requirements
- 6-ft. (183 cm) power cord attached on underside of unit for ease of countertop placement
- Coated aluminum wells offer easy cleaning and longer life
- Holds 4 1/8 qt. insets (Inset item #78164)
- Replaces Vollrath Models TW-665 and TW-24
- Meets NSF4 performance standards (hinged cover is not NSF certified)
- Stainless exterior for easy cleaning

**MODEL SS-4 WARMER FEATURES**

- Coated aluminum well
- Holds 4 1/8 qt. (3.9L) insets
- Holds No. 10 cans
- Ideal for ice cream toppings and nacho cheese sauce
- Meets NSF4 performance standards


**DESCRIPTION**

Servers are designed to hold 4 1/8 qt. insets to provide greater flexibility with a minimum of space required. All operate on 120V, 15A service.


**DIMENSIONS AND RATINGS**

Item	Description	Maximum Dimensions (L X W X H) IN (CM)	Voltage	Watts	Amps	Plug	Case Lot
72045	Twin Well 4 qt. Rethermalizer	17 1/4 x 9 1/4 x 8 3/4 (43.8 x 23.5 x 22.2)	120V AC	550 per well	9.2	5-15P	1
72040	Twin Well 4 qt. Rethermalizer, package w/ two insets (78164) and two hinged covers (47486)	17 1/4 x 9 1/4 x 12 1/4 (43.8 x 23.5 x 31.1)	120V AC	550 per well	9.2	5-15P	1
		<b>Dia. X H</b>					
72425	SS-4 Warmer only	8 3/4 x 7 7/8 (22.2 x 20)	120V AC	350	3.0	5-15P	1
72430	SS-4 with inset (78164), cover (78160), and hinge (72222)		120V AC	350	3.0	5-15P	1

Receptacle



**Agency Listings**



**Approvals**

---

Date: \_\_\_\_\_



www.vollrathco.com

The Vollrath Company, L.L.C.  
 1236 North 18th Street  
 Sheboygan, WI 53082-0611  
 U.S.A.  
 Main Tel: 800.624.2051  
 Service Tel: 800.628.0832  
 FAX: 800.752.5620

Vollrath of Canada, Co.  
 Tel: 800.695.8560  
 FAX: 800.752.5620