## ELECTRIC GRIDDLES

Spectrum griddles have a wide heating range, from frying eggs on low to cooking burgers with high heat, all on the half-inch thick polished steel grill surface. Independent controls further regulate the heating zones. The extra-tall steel wall backsplash enclosure helps to minimize grease splatters.

- Solid 1/2" thick polished steel plate for fast heat up and high heat retention
- Heavy gauge stainless steel body with 3" high backsplash; sides taper back to front
- Large-volume removable grease drawer with weep hole and baffle
- Heavy duty, stainless steel adjustable legs for stability
- Compatible for 1-phase or 3-phase operation (field convertible EGD-24M & EGD-36M)
- ♦ 3-1/4" full width grease trough

	ITEM	OVERALL DIMENSIONS L" X D" X H" (mm)	POWER	PLUG	SHIP WEIGHT
	EGD-16M*	16 x 19-¹/ <sub>8</sub> x 12-²/ <sub>8</sub> (406 x 486 x327)		NEMA 5-15P	53 lbs
			120V 50/60 Hz 1750W 14.6A	NEMA 5-20P (Canada)	(24 kgs)
	EGD-24M**	24 x 21-¾ x 12-7/8 (610 x 551 x 327)	208/240V~ 50/60 Hz, 4200/5600W, 20.2/23.4A, 1-phase	NEMA L6-30P	116.84 lbs (53 kg)
	EGD-36M**	36 x 21-¾ x 12- <sup>7</sup> / <sub>8</sub> (913 x 551 x 327)	208/240V~ 50/60 Hz, 6300/8400W, 30.29/35A, 1-phase	Field-wired by others	159.61 lbs (72.4 kg)

\*Cooking surface depth 15-1/8"(384mm) \*\*Cooking surface depth 16-1/2"(419mm)

	ITEM	DESCRIPTION	UOM	CASE
	EGD-16M	16" Griddle, 1 Heat Zone	Set	1
⋗▶	EGD-24M	24" Griddle, 2 Heat Zones	Set	1
AND COL	EGD-36M	36" Griddle, 3 Heat Zones	Set	1
	EGD-MP6	Replacement Knob	Each	1
	EGD-MP19	NEMA 5-20P cord for EGD-16M	Each	1





## GAS STOCK POT STOVE, FLOOR USE

Designed for the kitchen that has limited space and requires a low work height for large pots. This unit is equipped with a high-performance triple-ring burner, heavy duty single-piece cast iron top grate, removable crumb tray and a storage area below the control panel. Includes an LP conversion kit.

- High performance single (1) grate with three (3) concentric ring burners for a total output of 80,000 BTUH
- Dual infinite heat controls
- Stainless steel body, legs and drip pan
- Heavy duty cast iron grate
- Standing pilot ignition system with stainless steel pilots and pilot tubes
- 3/4" rear gas connection with regulator
- Convenient storage area in cabinet
- Conversion kit allows the use of propane or natural gas

ITEM	DESCRIPTION	UOM	CASE
🙈 NGSP-1	18" Gas Stock Pot Stove	Set	1
NG-Knob	Replacement Metal Knob	Each	1

	# OF BURNERS	# OF RINGS	BTU/PER NAT/LP	total BTU/HR	PRESSURE IN. W.C.	DIMENSIONS* L" x D" x H" (mm)	GRATE SURFACE L" x D" (mm)	SHIP WEIGHT	S
N	2	3	40,000	80,000	5 / 10	18 x 21-3/8 x 253/4 (455 x 543 x 653)	17¾ x 21-3/8 (450 x 543)	132 lbs (60 kgs)	SANITAT
	Note: Depths do not include gas inlet pipe, located at rear of the unit.								







SPECTRUM

2 infinite heat

GAS STOCK POT STOVE