# MOFFETT E311MS

## Half Size Electric Convection Oven





Stainless steel door with full viewing window

Stay cool heavy duty stainless steel door handle

4 half pan capacity

60 minute bake timer

3 hour roast timer

S Cook n hold system

Insulated porcelain inner

Internal lighting

Water injected steam (hook-up optional)

S Broiling element



**E311MS** 



Order Toll Free 1800 551 8795

#### E311MS

Unit shall be a Moffat electrically heated Turbofan convection oven E.T.L listed (UL Std 197) and NSF listed (NSF-4). The oven shall have a one piece vitreous porcelain enamel oven liner, stainless steel top and sides with single stainless steel door and full viewing window. Oven liner shall be insulated on all sides and have capacity for four half size sheet pans. A single speed fan shall evenly circulate air internally.

The oven shall be controlled by a mechanical thermostat with a range from 150°F to 525°F, have a broil switch built into the thermostat, a 60 minute bake timer, 3 hour cook n hold timer, push button water injection and oven light switch. Oven shall be able to be bench mounted on 4" legs or on Moffat's A25 stand. Oven shall be fitted with a NEMA 6-15P cordset.

## MOFFRT E311MS

## Half Size Electric Convection Oven

#### CONSTRUCTION

Stainless steel top and sides Porcelain oven interior Toughened twin pane door glass Strong and stylish door handle 4 half pan capacity (wire racks included) Fully insulated Stainless steel control panel with overlay

Fully enclosed motor at rear

#### CONTROLS

On/off switch

Mechanical thermostat, variable between 150°F to 525°F

3 hour roast timer

Cook n hold factory preset at 158°F (range 140°F to 194°F)

Water injection steam (momentary switch) Low velocity fan system

Broil position for cheesemelting/toasting Oven light

#### CLEANING AND SERVICING

Fully removable racks and fan baffle Fully removable bottom element guard Easy clean surfaces Access to all controls from front panel No tools required to replace lamps Removable gaskets - no tools required

#### OPTIONS

Stand with casters Half size sheet pans

#### SPECIFICATIONS

**Electrical requirements** 

208V, 60Hz, 1P+N+E, 2.9kW,14.0A 220-240V, 60Hz, 1P+N+E, 3.1kW,13.0A NEMA 6-15P cordset fitted

#### Water

3/4" thread

80psi max inlet pressure 20psi min inlet pressure

#### **External Dimensions**

Width 313/8" (796mm) 227/8" (567mm) Height 235/8" (600mm) Depth

#### Internal Dimensions

Width 211/2" (544mm) 161/2" (418mm) Height 151/s" (385mm) Depth

#### Oven Back Dimensions

Width 207/8" (530mm) Depth 141/2" (370mm)

### **Nett Weight**

189lbs (86kg)

### **Packing Data**

227lbs (103kg) 14.5ft<sup>3</sup> (0.41m3) 327/8"(835mm) Width Height 281/2"(720mm) Depth 271/4" (690mm)



www.moffat.com


U.S.A Moffat Inc 3765 Champion Boulevard Winston-Salem North Carolina 27105 Call Free 1800 551 8795 Ph 336-661 0257 Fax 336-661 9546 Email sales@moffat.com www.moffat.com


Canada **Lessard Agencies Ltd** PO Box 97 Stn D Toronto Ontario M6P 3J5 Canada Call Free 1888 LESSARD Ph 416-766 2764 Fax 416-760 0394


Australia **Moffat Pty Limited** 740 Springvale Rd Mulgrave Victoria 3170 Australia Ph 03-9518 3888 Fax 03-9518 3833 Email vsales@moffat.com.au www.moffat.com.au

**New Zealand** Moffat Limited 16 Osborne St PO Box 10-001 Christchurch New Zealand Ph 03-389 1007 Fax 03-389 1276 Email sales@moffat.co.nz www.moffat.co.nz

United Kingdom Blue Seal Limited Units 6-7 Mount St **Business Park** Birmingham B7 5QU England Ph 0121-327 5575 Fax 0121-327 9711 Email sales@blue-seal.co.uk www.blue-seal.co.uk













All Turbofan products are designed and manufactured by Moffat Ltd using the internationally recognised ISO 9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

