

# Top Mount Series

## Top Mount Freezer

### Digitally Controlled Uniform Temperature Economical Size and Design

- \* **Top Mounted Compressor**
- \* **Digitally Controlled Temperature**  
Freshness of products lasts longer by keeping the correct temperature.
- \* **LED Display**  
Shows exact temperature reading of the unit.
- \* **Stainless Steel**  
Stainless steel bottom surface.  
Aluminium wall construction.
- \* **Efficient Refrigeration System**  
Green World's solid freezers are designed with over-sized evaporators and condensers for faster cooling and greater efficiency.
- \* **CFC Free**  
All Green World's freezers are foamed in place with high density, close cell, poly-urethane that is CFC free.
- \* **Freezer holds -10°F**
- \* **Recessed Handles**  
Green World's recessed handle enhances our products aesthetically and functionally.



GST-40DF



GST-20SF



GST-60TF



Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Weight	L D H	List Price
GST-20SF	1	19	3	1/3	4.6	220	25.15 x 32.3 x 70.35	3,941.00
GST-40DF	2	40	6	1/2	8.5	352.7	49.52 x 32.3 x 70.35	5,614.00
GST-60TF	3	60	9	1	4.4	682	74.8 x 32.3 x 70.35	7,965.00

\* Height does not include 5" for caster height.

**CABINET INTERIOR/EXTERIOR SPECIFICATIONS**

ELECTRICAL DATA	GST-20SF	GST-40DF	GST-60TF
Voltage	115V/60Hz	115V/60Hz	115V/208~220V/60Hz
Feed Wires(With ground)	3	3	3
Wattage	374	778	965
Amperes	4.58 A	8.45 A	4.4 A
<b>SHIPPING DATA</b>			
Length-Crated(in)	27.9	52.4	77.4
Depth-Crated(in)	34.5	34.5	35.2
Height-Crated(in)	75.5	75.5	75.5
Volume Crated(cu.ft)	42.0	78.9	119.0
Net Weight(lbs)	220	352.7	682
Weight After Packing (lbs)	243	374.8	738.5
<b>DIMENSIONAL DATA</b>			
# of Doors	1	2	3
Cubic Feet	17.3	36	56.3
Rack capacity	1	2	3
Length Overall (in)	25.15	49.52	74.8
Depth Overall (in)	32.3	32.3	32.3
Height Overall (in)(with caster)	75.35	75.35	75.35
Interior Dimension (LxDxH)	21.6x25.5x54.2	46.6x25.5x54.2	70.4x25.5x54.2
Shelf Size	20.5x22	22x24.2	22x24.2(6ea) 24.1x24.2(3ea)
# of Shelves	3	6	9

**\* Other Features**

- Minimum wattage heater in the cabinet frame to conserve energy and keep your cabinet water free.
- Incandescent interior lighting.
- Positive seal with self-closing doors.
- Automatic evaporator fan motor delay when the door is opened.
- The defrost systems are time initiated and temperature terminated.
- Door locks standard.

\*Design and specifications can be changed without prior notice for product improvement.

