

Job	Item No.

# Ice Pans Non-Refrigerated Cold Pans

□ ICP-100 □ ICP-200 □ ICP-300 □ ICP-400 □ ICP-500 □ ICP-600

# STANDARD FEATURES

- □ Drop-in design
- NSF-2 compliant
- ☐ Hold standard 12" by 20" food pans and fractional sized pans
- □ 18 gauge stainless steel top and liner for maximum strength and durability
- ☐ 1" drains per well for ease of cleaning
- Perforated bottom strainer plate conveniently holds ice above drain for ease of cleaning
- ☐ CFC free fully insulated
- ☐ Foamed-in place insulation keeps food cold while saving energy
- ☐ Recessed ledge for pan support and colder, fresher products
- ☐ Limited 1 year parts and labor warranty

### **OPTIONS & ACCESSORIES**

- ☐ Divider bars for fractional pans
- ☐ 2nd year parts & labor warranty

#### **CERTIFICATIONS**





Model ICP-300

## **DESCRIPTION**

Wells Non-Refrigerated Drop-In Ice Pans are designed to hold pre-chilled food products at serving temperatures. All models are completely self-contained in one to six-well models featuring CFC free insulation. Recessed top ledges lowers inset pans; keeping food colder and fresher and meet NSF-2 guidelines.

#### **SPECIFICATIONS**

**Exterior** – One-piece top flange and coved-corner interiors constructed of 18 gauge stainless steel. Exterior body constructed of heavy gauge, corrosion resistant steel.

**Interior** – CFC free foamed-in-place insulation through-out. Each pan features a 1" drain located in the center for easy cleaning, and recessed ledges for pan support.


Sheet No. WELLSICP-02/12







# Non-Refrigerated Cold Pans □ ICP-100 □ ICP-200 □ ICP-300

□ ICP-400 □ ICP-500 □ ICP-600









**ICP-300 SHOWN** 

**ISOMETRIC VIEW** 







**FRONT ELEVATION** 

OTE: Specifications are subject to change without notice and are not intended for installation purposes. See installation instructions prior to installing the unit.

SPECIFICATIONS								SHIPPING INFORMATION							
	OVERALL DIMENSIONS			INTERIOR DIMENSIONS		CUT OUT DIMENSIONS			WEIGHTS		CARTON DIMENSIONS			CRATE SIZE	
Model Number	A Front to Back Inches (MM)	B Left to Right Inches (MM)	C Height Inches (MM)	D Front to Back Inches (MM)	E Left to Right Inches (MM)	Width Front to Back Inches (MM)	Length Left to Right Inches (MM)	Model Number	SHIPPING WEIGHT POUNDS (KG)	INSTALLED WEIGHT POUNDS (KG)	WIDTH Inches (MM)	DEPTH Inches (MM)	HEIGHT Inches (MM)	CUBIC FEET	CUBIC METERS
ICP-100	25-3/8 (645)	17-3/8 (441)	9-3/4 (248)	19-7/8 (505)	11-7/8 (301)	23-7/8 (606)	15-7/8 (403)	ICP-100	89 (40)	84 (38)	19 (482)	27 (686)	32 (813)	9.5	0.27
ICP-200	25-3/8 (645)	31 (787)	9-3/4 (248)	19-7/8 (505)	25-1/2 (648)	23-7/8 (606)	29-1/2 (749)	ICP-200	182 (83)	176 (80)	27 (686)	32 (813)	32 (813)	16.0	0.46
ICP-300	25-3/8 (645)	44-3/4 (1137)	9-3/4 (248)	19-7/8 (505)	39-1/4 (997)	23-7/8 (606)	43-1/4 (1099)	ICP-300	194 (88)	187 (85)	27 (686)	46 (1168)	32 (813)	23.0	0.65
ICP-400	25-3/8 (645)	58-1/2 (1486)	9-3/4 (248)	19-7/8 (505)	53 (1346)	23-7/8 (606)	57 (1448)	ICP-400	258 (117)	250 (113)	27 (686)	60 (1524)	32 (813)	30.0	0.85
ICP-500	25-3/8 (645)	72-1/4 (1847)	9-3/4 (248)	19-7/8 (505)	66-3/4 (1695)	23-7/8 (606)	70-3/4 (1797)	ICP-500	278 (126)	269 (122)	27 (686)	73 (1854)	32 (813)	36.5	1.04
ICP-600	25-3/8 (645)	86 (2184)	9-3/4 (248)	19-7/8 (505)	80-1/2 (2045)	23-7/8 (606)	84-1/2 (2146)	ICP-600	290 (154)	280 (109)	27 (686)	87 (2210)	32 (813)	43.5	1.23

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While Wells exercises good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using the specifications. By using the information provided, the user assumes all risks in connection with such use.



Wells Bloomfield • 10 Sunnen Dr. St. Louis, MO 63143 U.S.A. Phone: (314) 678-6314 • Fax (314) 781-3636

www.wellsbloomfield.com © 2012 Wells Bloomfield • Printed in the U.S.A.