

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model # :		
Item #:	Qty:	
Available W/H :		
Approval :		

## Solid Door Refrigerator

Reach-In Top Mount

J Series

Model: JR45-2

#### \_\_\_ FEATURES & BENEFITS =\_\_

### ■ Digital temperature control system

Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

#### ■ High-tech monitor

The monitor digitally displays present cabinet temperatures. You can easily change the temperature by adjusting the thermostat.

#### ■ Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also prevents the overflow of condensate water.

#### ■ Door pressure release device

Pressure relief doors are designed to eliminates vacuum pressure and allows easy, instant door opening.

#### ■ LED interior lighting system

Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents. It saves energy by producing less heat, while maximizing the visibility.

#### ■ Efficient refrigeration system

Turbo Air's J series solid door refrigerators are designed with oversized and balanced (CFC Free R-134A) refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

#### Automatic evaporator fan motor delays

When the door is opened the evaporator fan will stop, preventing the circulation of hot and moist air from escaping into the refrigerator. This increases energy efficiency and lengthens the life of the compressor.

#### Adjustable, heavy duty, PE(polyethylene) coated wire shelves

#### Exterior & interior of cabinet construction

Stainless steel exterior (galvanized steel top, bottom and back) and stainless steel interior with AL inside walls and door liners. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, the sharp corners and edges have been rounded to reduce the risk of injury.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.



Refrigerator holds 33°F ~ 38°F for the best in food preservation









	Interver.						
Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H † (inches)
JR45-2	2	42.9	6	1/4	5.5	325	495/8 x 311/2 x 72

(unit: inch)

# Solid Door Refrigerator

## Model: JR45-2

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	① NEMA 5-15P				
Full Load Amperes	5.5				
Compressor HP	1/4				
Feed Wires with Ground	3				
Cord Length ft.	9				
Refrigerant	R-134A				
DIMENSIONAL DATA					
# of Doors	2				
Net Capacity cu. ft.	42.9				
Ext. Length Overall in.	495/8 (1260mm)				
Ext. Depth Overall in.*	311/2 (800mm)				
Ext. Height Overall in.†	72 (1829mm)				
Int. Length Overall in.	46 (1170mm)				
Int. Depth Overall in.	273/8 (695mm)				
Int. Height Overall in.	521/2 (1333mm)				
Gross Weight lbs.	312				
Net Weight lbs.	325				
# of Shelves	6				
Self Size	223/8 x 241/2				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.


#### 2 Year Parts and Labor Warranty WARRANTY: **Additional 3 Year Warranty on Compressor**


- Door locks standard
- Self-contained system
- Standard 4" swivel casters with locks on the front set
- Solid and sturdy grille design
- Legs available for all models (optional)

#### ■ OPTIONAL ACCESSORIES:

- 2.5" Diameter casters
- □ 5" Diameter casters
- ☐ 6" ABS plastic legs
- ☐ Additional PE coated wire shelves

### **PLAN VIEW**





Ver 201501














■ Warranty: 800-381-7770 ■ AC: 888-900-1002









<sup>\*</sup> Depth does not include 2" for rear condensate enclosure. † Height does not include 5" for caster height.