

1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

LUMAVUE SERIES—GLASS DOOR MERCHANDISER

Used for merchandising and storage of product.

CABINET CONSTRUCTION

Heavy duty construction includes white coated steel interior walls. Exterior finish is heavy-duty steel with a baked on durable coating. Choose from black or white finish.

2" foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

Modern, one-piece grille is easily removed for cleaning and servicing.

Double pane, lowE argon filled glass door features inside and outside panes that are tempered for added safety.

Self-closing, hinged glass door features recessed, pocket door handle provides low profile and is more aesthetically pleasing. Door provides automatic hold-open feature.

Four white epoxy coated steel shelves are standard.

REFRIGERATION

Whisper-quiet refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.

Product temperatures from 32°F to 40°F.

ELECTRICAL

Interior fluorescent lighting enhances product illumination. Optional LED lighting provides hidden light source for increased product visibility. LED bulbs last up to 10 times longer compared to fluorescent bulbs and renders additional energy savings due to reduced wattage load on compressor.

Units wired at factory and ready for connection to a **ELECTRICAL CONNECTION** 115/60/1 phase, 15 amp Units pre-wired at factory and include dedicated outlet. 8' long | 8' long cord and plug set. cord and plug set included.



115/60/1 NEMA-5-15P












*Note: Not all markings may apply to all model variations.



HINGED GLASS DOOR **LUMAVUE**[™] MERCHANDISER SERIES LV12

MODELS: LV12-1-B LV12-1-W LV12-1-B-LED LV12-1-W-LED



LV12-1-B

SPECIAL FEATURES

- Whisper-quiet refrigeration system
- Recessed, pocket door handle
- Optional LED lighting
- 2010 Federal Energy Compliant
- Gravity Flo kits and Can Roller options available

Available From:

Model Specified	Store#
Location	Quantity



LumaVue Glass Door Merchandisers Model: LV12

MODEL	LV12
EXTERNAL DIMENSIONAL DATA	
Length Overall (inches) Length Overall (mm)	24" 610
Depth Overall (inches) Depth Overall (mm)	24" 610
Height Overall— (inches) Height Overall— (mm)	62" 1575
Number of doors	1
Depth with Door Open 90 °	n/a*
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.) NET Capacity (Liters)	12 340
Internal Length Overall (inches) Internal Length Overall (mm)	21" 533
Internal Depth Overall (inches) Internal Depth Overall (mm)	20 3/4" 527
Internal Height Overall—(inches) Internal Height Overall—(mm)	45 3/4" 1162
Number of shelves	4
ELECTRICAL DATA	
Full Load Amperes 115/60/1	5.0 A
ENERGY CONSUMPTION	3.1 kWh/Day
REFRIGERATION DATA	
Horsepower	1/6
WEIGHT DATA	
Gross Weight (Crated lbs)	230
Gross Weight (Crated kg)	104











Note: Not all markings may apply to all model variations.

*N/A:: Not available at time of printing.

PLAN VIEWS

