

Heater Proofers - Non-Insulated

Economy

100% Pre-Tested Electrical Assembly

Equipment Guide

- ✓ GOOD
- ✓ MEDIUM DUTY USE
- ✓ 1YR WARRANTY
- ✓ HACCP HELPER
- ✓  
- ✓ **NEW**
- ✓ **EXPRESS SHIP**

- Heavy Duty, channel construction designed for durability. Easy to Clean.
- Air baffle and circulating air blower provide even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Two locking casters in front.
- Easy dual proof/heat control:
 "Proof" mode: Humidity from 30% to 95%.
 Temperatures up to 115°F (46°C)
 "Heat" mode: Nominal Temperatures up to 180°F (82°C)
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on inside door frame, held closed with magnets, Lexan fits tightly into door frame.
- Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- All controls are accessible without opening cabinet door.
- Easy to read LED thermometer.
- Pan Capacity: 36 - 18" x 26" pans

Electrical specifications:

- 120 Volt-60 Cycle A.C.
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



NHP-PD-ECO
 Removable Drawer
 Makes Cleaning Quick & Easy

On Both NHPL-1836-ECO & NHPL-1836 Units

Water Pan



Air baffle and circulating air blower provide even heat distribution.

Model Number	Order#	Overall Dimensions						Approx. Ship Wt	
		Width		Length		Height		(lb)	(kg)
		(in)	(mm)	(in)	(mm)	(in)	(mm)		
NHPL-1836-ECO	637795	21	533	30¾	781	68	1,727	235	106
Caster Information									
738A	128784	Swivel Plate Caster with 5" Polyurethane Wheel							
738ABK	204185	Swivel Plate Caster with 5" Polyurethane Wheel & Brake							
7112	122180	5" Polyurethane Wheel							

For replacement parts please see page 125.

Freight Class: 100

