



Potato peeler PI-10 - 120 V / 60 Hz / 1~ (without stand)

Easy to operate and reliable

Stainless steel construction. Chamber walls and base plate lined with highly resistant and long-lasting abrasive.

- Ease of use:
 - Simple manual switch with adjustable 6 minute timer.
 - On/off push buttons .
 - Pulse button to assist discharging peeled potatoes.
 - Lifiable transparent cover.
 - Auto drag of waste to drain.
 - Easy to clean.
- Increased durability:
 - Stainless steel construction.
 - Cast aluminum peeling disc.
 - Highly resistant NSF approved abrasive.
 - Waterproof control board (IP65).
- Safety:
 - Cover with locking and safety micro switch.
 - Aluminum door with hermetic seal and safety micro switch.
 - Water inlet system with non-return air break.
- Optional extra: Stainless steel floor stand.

COMPLETE WITH:

OPTIONAL:

A stainless steel stand complete with removable filter chamber.

Technical Data

Capacity per process:	22 lbs
Hourly output:	450/550 lbs/h
Timer:	0-6 min
Dimensions without stand	
-Width:	17"
-Depth:	25"
-Height:	24 5/8"
Dimensions with stand	
-Width:	17"
-Depth:	25 1/8"
-Height:	41"
Net Weight:	86lbs
Loading:	550 W / 3/4 Hp
Electrical supply:	120V / 60 Hz. / 1~



UNE-EN ISO 9001

SAMMIC, S.L. (Sociedad Unipersonal) □
Basarte, 1 - 20720 AZKOITIA - www.sammic.com

European directives
93/68 CEE, 2006/95/CE

Norms
UNE-EN 60335-1, UNE-EN 60335-2-64, EN 55014-1, EN 55014-2,
EN 61000-3-2, NSF/ANSI Estándar 169.