



Potato peeler PI-30 120/60/1

Easy to operate and reliable.

Stainless steel construction. Base plate and lateral stirrers lined with highly resistant and long-lasting abrasive.

- Ease of use:
 - Simple manual switch with adjustable 6 minute timer.
 - On/off push buttons .
 - Pulse button to assist discharging peeled potatoes.
 - Lifiable transparent cover.
 - Auto drag of waste to drain.
 - Easy to clean.
 - Water inlet system fitted with electric valve.
- Increased durability:
 - Stainless steel construction.
 - Cast aluminum peeling disc.
 - Highly resistant NSF approved abrasive.
 - Waterproof control board (IP65).
 - Abrasive lateral stirrers.
- Safety:
 - Cover with locking and safety micro switch.
 - Aluminum door with hermetic seal and safety micro switch.
 - Water inlet system with non-return air break.
- Optional extra: Stainless steel floor stand.

COMPLETE WITH:
OPTIONAL:

A stainless steel stand complete with removable filter chamber.

Technical Data

Capacity per process:	66 lbs
Hourly output:	1300/1600 lbs/h
Timer:	0-6 min
Dimensions without stand	
-Width:	24 1/2"
-Depth:	29 7/8"
-Height:	37 3/8"
Dimensions with stand	
-Width:	21 1/2"
-Depth:	29 7/8"
-Height:	49" 3/8"
Net Weight:	132 2/4 lbs
Loading:	730 W / 1 Hp
Electrical supply:	120V / 60 Hz. / 1~


 Empresa Registrada
 ER-0437/1.96

UNE-EN ISO 9001

 SAMMIC, S.L. (Sociedad Unipersonal) □
 Basarte, 1 - 20720 AZKOITIA - www.sammic.com

 European directives
 93/68 CEE, 2006/95/CE

 Norms
 UNE-EN 60335-1, UNE-EN 60335-2-64, EN 55014-1, EN 55014-2,
 EN 61000-3-2, NSF/ANSI Estándar 169.