

• PRODUCT SPECIFICATIONS SHEETS



• Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity

Self-Contained Remote	SC-OP30E-3-LS R-OP30E-3-LS	SC-OP30E-4-LS R-OP30E-4-LS	SC-OP30E-6-LS R-OP30E-6-LS	SC-OP30E-8-LS R-OP30E-8-LS
Length with ends	39"	51"	75"	99"
Length without ends	36"	48"	72"	96"
Height with ends	72"	72"	72"	72"
Depth with ends	30"	30"	30"	30"
(Dimensions are +/-1/4	")			

• Specification subject to change without notice



Standard Specifications and Optional Features

CONSTRUCTION UL Classified to ANSI/NSF 7 Foamed in place CFC free foam Heavy gauge steel super structure Multi deck Endless design allows for continuous line up	FINISHES Designer white or black end panels Designer white or black front bumper Designer white or black end trim Coated galvanized rear
INTERIOR Designer white or black end panels Removable designer white or black floor racks Designer white or black perforated rear wall (for even air distribution) Full length lighting at top of unit 1 level of 14" shelving with product stops Full length mirror to enhance product display Stylish tag molding on shelf	REFRIGERATION R404A expansion valve system Low velocity fans located below deck area (to insure even flow of air) Pressure control maintains constant temperatures Automatic defrost controlled by time clock (self contained units only) Air screen technology Self contained system Copeland hermetic unit Remotes available
EXTERIOR Designer white or black ends and front Designer white or black bumper Designer white or black end trim Removable front grille for cleaning and servicing Plexiglas on end panel	LIGHTING 1 row at inside top of unit 1 lighted shelf with product stop
ELECTRICAL REQUIREMENTS Unit must be hard wired UL/CUL Listed See technical page for voltage	Important Note: All refrigerated cases are designed to operate in an environment of 75 degrees and 55% relative humidity. Important Note: DRAIN IS REQUIRED

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

OPTIONAL FEATURES

Night cover	Stainless steel, laminate or colors
Peg bars	Security cover
Condensate pan (4' case only) Insulated divider for line ups Electronic control system	Plexiglas divider for line ups Digital thermometer





Technical Data

Model	Self contained	SC-OP30E-3-LS	SC-OP30E-4-LS	SC-OP30E-6-LS	SC-OP30E-8-LS
	Remote	R-OP30E-3-LS	R-OP30E-4-LS	R-OP30E-6-LS	R-OP30E-8-LS
Length with ends Length without ends Height with ends Depth with ends (Dimensions are +/- 1/4")		39" 36" 72" 30"	51" 48" 72 " 30"	75" 72" 72 " 30"	99" 96" 72 " 30"
Operating temperature Refrigerant (expansion valve) Compressor size- HP Pressure control settings @ 75°F, 55%RH Defrost per day (24 hrs) BTU's at +20°F Evap. Temp. Voltage Amperage Amperage, lights & fans Cord and plug	Self contained Self contained CUT IN CUT OUT Hours @ 12pm Remote Self contained Remote	54	38°F to 41°F R404A 1/2 88 54 3 @ 30 min. 4000 115V 12.4A 1.7A No	38°F to 41°F R404A 3/4 88 54 3 @ 30 min. 6000 115V 13.5A 2.0A No	38°F to 41°F R404A 3/4 88 54 3 @ 30 min. 8000 115/208-230V 12.5A 3.4A No
Exterior color Interior color Inside end panels Floors		White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black	White or Black White or Black White or Black White or Black

(ALL WHITE OR ALL BLACK, NO EXTRA CHARGE—IF COLORS ARE MIXED AN ADDITIONAL CHARGE WILL APPLY)

SHIPPING INFORMATION

Height		76"	76"	76"	76"
Depth Length		44" 61"	44" 61"	44" 87"	44" 109"
Gross weight	Self contained	525#	605#	850#	1075#
	Remote	400#	480#	700#	900#
Cubic feet		115ft ³	115ft ³	166ft³	206ft ³

- · Cases are designed to operate at 75 degrees Fahrenheit and 55% relative humidity
- · Cases are equipped with drains; check your local building codes for connection requirements.
- · Specification subject to change without notice



Technical Data • Side View • Plan View

