Anets SilverLine™ Manual Gas Griddle

SLMG Models

Item No.

Anets Introduces A Griddle Designed for Years Of Outstanding Performance

The reliable Anets heavy duty stainless steel construction is ready for your busy kitchen. Dependable manual valves put temperature control in the operators hands. Convenient viewing ports enable the user to see the burner flame for straight forward flame control. The standing pilot ignition system is easily accessible through individual access points. One Ushaped burner for every foot of griddle width provides even heat distribution across entire griddle surface and heat zone control. Available in a variety of sizes. Get Anets quality at an affordable price, the Anets manually controlled griddle.

STANDARD FEATURES

- High nickel content 3/4" precision ground hot rolled steel plate
- One burner per foot: 30,000 BTUH per burner
- Stainless steel front, sides, grease trough, and splashguards
- No electrical connections required
- Extra large grease chute opening
- Large capacity 5.7 quart grease drawer easily accessible under cabinet and is equipped with antisplash guards
- Double wall construction keeps the operator and kitchen cool
- Equipped with an easy to reach main gas shut-off valve





SLMG 24x36 shown

undershelf and casters

optional stainless steel stand with





Anets SilverLine™ Manual Gas Griddle

SLMG Models



SPECIFICATIONS

- Model
- Certification
- BTUH input
- Gas Supply Pressure
- Gas Connection
- Electrical
- Plate
- Burners
- Cabinet

SLMG Models (See chart below)

ETL, CETL

30,000 per burner (foot),

NG 4" WC, LP 10" WC,

Pressure regulator included

3/4" NPT

None

High nickel content 3/4" precision ground

hot rolled steel plate

Aluminized steel

Front, sides, trough and

splashguard, stainless steel

Back, aluminized steel

STANDARD ACCESSORIES

- Stainless steel sides
- Pressure regulator
- 4" Adjustable chrome plated legs

OPTIONS AND ACCESSORIES

- Removable cutting board and bracket assembly

Stainless steel stands

DIMENSIONS

24" MODELS

| | SLMG | SLMG | SLMG |
|-------------|--------|--------|---------|
| Overall | 24X24 | 24X36 | 24X48 |
| ■ (W) Width | 24.25" | 36.25" | 48.25" |
| Height | 17.25" | 17.25" | 17.25" |
| ■ Depth | 29.5" | 29.5" | 29.5" |
| Plate | | | |
| ■ Width | 24" | 36" | 48" |
| ■ (D) Depth | 24" | 24" | 24" |
| NG BTUH | 60,000 | 90,000 | 120,000 |
| LP BTUH | 60,000 | 90.000 | 120,000 |

Specifications subject to change without notice. SS# 204 Revised 8/05 Printed in the U.S.A.



