



FOOD PREPARATION

Ref.1140436

VACUUM PACKING MACHINES





Ready to use Vac-Norm external vacuum kit.



Deep drawn chamber (300/400 series)



Cordless sealing bar in all models.

Vacuum packing machine SV-410S 120/60/1

Table top unit

- · Length: sealing bar of 16"
- · Microprocessor: Control exact vacuum percentage in chamber.
- · Plus vacuum: allows to program an extra vacuum time period once 99% vacuum has been reached.
- · LEDs indicate each cycle stage whilst performing.
- · A STOP key allows the interruption of the cycle at any stage, moving on to the next step.
- · Easy to program. 10-program-memory.
- · Softair with independent valve & gas flushing.
- · Deep-drawn chamber.
- · Cordless sealing bar.
- · Pump drying program, improving durability.
- · Working hours counter display, informing when oil must be replaced.
- Ready to use Vac-Norm external vacuum kit.

Technical Data

Vacuum pump: 350 cf/h
Sealing type: Double
Sealing bar length: 16"
Electrical loading: 1 1/4 Hp
Vacuum pressure (maxi): 2 mbar

Chamber dimensions:

-Width: 17"
-Depth: 16"
-Height: 6"

External dimensions:

-Width: 20" -Depth: 20" -Height: 16"

Net weight: 141 lbs.

ELECTRICAL SUPPLY: 120V / 60Hz /1~

COMPLETE WITH:

Insert plate set

OPTIONAL:

- · Vac-Norm external vacuum kit
- · Bag cutting kit
- · Liquid insert plate set











SAMMIC, S.L. (Sociedad Unipersonal)

European directives 2006/42/CE, 93/68 CEE 2006/95/CE

Norms UNE-EN 60335-1, UNE-EN 60335-2-64, EN 55014-1, EN 55014-2, EN 61000-3-2, NSF/ANSI Estándar 169.