



Ready to use Vac-Norm external vacuum kit.



Deep drawn chamber (300/400 series)



Cordless sealing bar in all models.

## Vacuum packing machine SV-420S 120/60/1

Table top unit

- Length: sealing bar of 16"

- Microprocessor: Control exact vacuum percentage in chamber.
- Plus vacuum: allows to program an extra vacuum time period once 99% vacuum has been reached.
- LEDs indicate each cycle stage whilst performing.
- A STOP key allows the interruption of the cycle at any stage, moving on to the next step.
- Easy to program. 10-program-memory.
- Softair with independent valve & gas flushing.
- Deep-drawn chamber.
- Cordless sealing bar.
- Pump drying program, improving durability.
- Working hours counter display, informing when oil must be replaced.
- Ready to use Vac-Norm external vacuum kit.

### Technical Data

Vacuum pump:	700 cf/h
Sealing type:	Double
Sealing bar length:	16"
Electrical loading:	1 1/4 Hp
Vacuum pressure (maxi):	2 mbar

Chamber dimensions:	
-Width:	17"
-Depth:	16"
-Height:	7"

External dimensions:	
-Width:	20"
-Depth:	20"
-Height:	18"

Net weight:	154 lbs.
-------------	----------

ELECTRICAL SUPPLY:	120V / 60Hz / 1~
--------------------	------------------

**COMPLETE WITH:**

Insert plate set

**OPTIONAL:**

- Vac-Norm external vacuum kit
- Bag cutting kit
- Liquid insert plate set


 ER  
 Empresa Registrada  
 ER-0437/196

**UNE-EN ISO 9001**

 SAMMIC, S.L. (Sociedad Unipersonal) □  
 Basarte, 1 - 20720 AZKOITIA - www.sammic.com

 European directives  
 2006/42/CE, 93/68 CEE,  
 2006/95/CE

 Norms  
 UNE-EN 60335-1, UNE-EN 60335-2-64, EN 55014-1, EN 55014-2,  
 EN 61000-3-2, NSF/ANSI Estándar 169.