HOLDING & TRANSPORT

VULCAN



UL listed. UL listed to Canadian safety standards. Classified by UL to NSF Std. #4.

I ISTED

SPECIFICATIONS

Vulcan Hart Model No. VPT pass through holding cabinets. Blower motor for gentle and even temperature distribution. Complete with 5" heavy duty casters (2 swivel with brakes and 2 rigid). Recessed control panel containing heating indicator light, analog thermometer, and full range thermostat for temperatures up to 190°F (88°C). Cabinet will hold 18" x 26" sheet pans, 12" x 20" steam table pans, or a combination of both on 11/2" centers. Complete with universal tray slides adjustable on 11/2" centers. Cabinet interior and exterior are both constructed out of 20 gauge stainless steel. Recessed side-mounted handles, magnetic action door latch, and full insulation; 11/2" in side walls and 2" in top. Integrated steel frame for maximum strength. Field reversible doors. Complete with top mounted cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts. Lifetime warranty on heating elements. □ VPT7 Holding & Transport Cabinet

Item #

VPT SERIES PASS THROUGH HOLDING CABINETS

- U VPT13 Holding & Transport Cabinet
- VPT15 Holding & Transport Cabinet

STANDARD FEATURES

- Pass-Thru Holding Capacity:
 - 18" x 26" sheet pans
 - 12" x 20" pans, or a combination of both on 11/2" centers
- Blower motor for gentle and even temperature distribution
- Dutch doors (VPT15 only)
- 5" heavy duty casters (2 swivel with brakes and 2 rigid)
- Recessed side mounted handles
- Recessed control panel
- Heating indicator light
- Analog thermometer
- Full range thermostat for temperatures up to 190°F (88°C)
- Universal tray slides adjustable on 1½" centers. VPT15 & VPT13 ship with 10 pairs of tray slides and VPT7 ships with five pairs.
- Interior and the exterior are both constructed out of 20 gauge stainless steel
- Fully insulated with 1¹/₂" in side walls and 2" in top
- Integrated steel frame for maximum strength
- Magnetic action door latch
- Field reversible doors
- Top mounted cord
- Complete with cord and plug: NEMA 5-15 for 120 volts and NEMA 6-15 for 208-240 volts
- Lifetime warranty on the heating elements

OPTIONS

- 208/240 volt
- Humidity pan
- □ Full perimeter bumper
- □ Glass Dutch doors (VPT15 & VPT7 only)
- □ VRH oven racking for VPT7, VPT15
- Wire shelves to sit on tray slides
- Electronic control with digital display (120V only)
- □ Transport latch (field installed)
- □ Additional tray slides

VULCAN

a division of ITW Food Equipment Group LLC

P.O. Box 696
Louisville, KY 40201
Toll-free: 1-800-814-2028
Local: 502-778-2791
Quote & Order Fax: 1-800-444-0602


A City Discount

HOLDING & TRANSPORT




VPT SERIES PASS THROUGH HOLDING CABINETS


Drawings shown with optional bumper




All Models Top View







VPT13 Front & Side Views



VPT15 Front & Side Views

MODEL	DIMENSIONS	CAPACITY		ELECTRICAL			SHIPPING WEIGHTS	
	EXTERIOR	12" x 20" x 2½" PANS	18" x 26" SHEET PANS	VOLTS	WATTS	AMPS	LBS	KG
VPT7	27" W x 34½" D x 40" H	14	7	120	1,000	8.3	198	90
VPT13	27" W x 34½" D x 61" H	26	13	120	1,200	10	270	123
VPT15	27" W x 34½" D x 66½" H	30	15	120	1,200	10	297	135

*per compartment

Optional bumper adds 31/4" to the width and 15/8" to the depth.



P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

F45415 (12/12)

NOTE: In line with its policy to continually improve its products, Vulcan reserves the right to change materials and specifications without notice.

A City Discount